

## 50" WIDE PLASMA DISPLAY

### SPECIFICATION

<b>Model</b>	P50XHA58EB		
<b>Screen size</b>	50" wide screen 110.6 cm (W) x 62.2 cm (H)		
<b>Aspect ratio</b>	16 : 9		
<b>Weight</b>	45Kg		
<b>Outer dimensions</b>	121.6 (W) x 72.6 (H) x 10.0 (D) cm (does not include outer projections)		
<b>Power supply</b>	120-240 VAC 50/60 Hz		
<b>Current rating</b>	4.85 - 1.95A		
<b>Number of pixels</b>	1366 (H) x 768 (V)		
<b>Corresponding signals</b>	RGB mode	VGA,WVGA,SVGA,XGA,WXGA,SXGA	
	Comp.video mode	SDTV 480i,576i,480P,576P / HDTV 720P,1080i	
	Video mode	NTSC,PAL,SECAM,M-PAL,N-PAL,PAL60,4.43NTSC	
<b>External equipment terminals</b>	VIDEO1 INPUT (Video)	RCA terminal	1 Vp-p/75
	VIDEO2 INPUT (S-Video)	S terminal	Y: 1 Vp-p/75 C: 0.286 Vp-p/75
	VIDEO3-4 INPUT	3 RCA terminal	Y: 1 Vp-p/75
	(Comp.video)	PB/CB: 0.7 Vp-p/75 , PR/CR: 0.7 Vp-p/75	
	VIDEO5-6 INPUT(HDMI)	HDMI terminal (HDMI type A connector)	
	RGB1 INPUT	mD-Sub , 3 rows, 15-pin	Picture signal: 0.7 Vp-p/75
	AUDIO1-3 INPUT	2 Pin jacks (L/R)	500 mVrms/at least 22k
	EXTERNAL SPEAKER OUTPUT	Max. output: 10 W + 10 W, 6	
	CONTROL TERMINAL	RS-232C D-sub9 PIN	
<b>Language (OSD)</b>	English , German , Spanish , French , Italian , Dutch , Greek		
<b>Operating conditions</b>	Temperature 0 to 40 , Humidity 20 to 80%		
<b>Regulations</b>	Safety	EN60065 , IEC60065	
	EMC	EN55022(CISPR22), Class B , EN61000-3-2 , EN61000-3-3 , EN55024(CISPR24)	
<b>Accessories</b>	2 user s manuals, 1 power cable, 2 small ferrite cores, 2 big ferrite cores, 1 remote control, 2 AA batteries		

<b>Options</b>	Wall-mounting Bracket	P-WB4201
	Ceiling unit	P-CT4200
	Desktop Stand unit	P-TT4202
	Speaker(1 set of 2 speakers)	P-SP1000 (for attaching to thedisplay)
		P-SP5010 (for mounting on the speaker stands)
	Desktop Speaker Stand	P-ST5000 (For P-SP5010)